



Pilkington **Profilit™** T

Pilkington **Profilit™** T Color



Pilkington **Profilit™**
Profiled glass with system

Pilkington **Profilit™** T and Pilkington **Profilit™** T Color

Creativity, design and safety for exterior- and interior glazing



Pilkington **Profilit™** T
thermally toughened Pilkington **Profilit™**
available with Heat Soak-test upon request



Pilkington **Profilit™** T Color
thermally toughened and
coloured enamelled Pilkington **Profilit™**
available with Heat Soak-test upon request



Pilkington **Profilit™** T and Pilkington **Profilit™** T Color offer:

- creativity, natural daylight and safety characteristics of a thermally toughened glass, especially for interior glazing and public assembly areas
- new design possibilities, e.g.: colour enamels Pilkington **Profilit™** T Color
- safety characteristics, e.g.: K25 tested acc. to the methodology of EN 12600
- higher mechanical resistance because of higher bending stresses
- new application possibilities, e.g.: office- and shop equipment, furniture, lamps, shelf systems, ... etc.

Note: The requirements for the application of thermally toughened Pilkington **Profilit™** in the various markets have to be checked by the installer with the local building authorities by taking into account the relevant national and international standards and regulations.



PILKINGTON
NSG Group Flat Glass Business

Bauglasindustrie GmbH

Hüttenstraße 33 66839 Schmelz

Phone +49 (0) 6887 303 0 Fax +49 (0) 6887 303 45 E-Mail profilbauglas@pilkington.de

www.pilkington.com